

**S-30 Overhead Door Closers Surface Mount**

TECHNICAL



Polished Nickel Plated




Satin Nickel Plated



Silver



Max:



The SPÄRKA S-30 Overhead Door Closer is an EN variable power size 2-5 door closer making it suitable for doors upto 1250mm wide / or maximum 110Kg. This door closer comes complete with mechanism, cover, armset, parallel arm bracket for mounting on the 'Push' face of the door, installation template and all fixings.

This model also has integrated adjustable valves to independently control the closing and latching speeds. Also with integrated back check valve which provides a cushioning effect for when the door opens too fast and integrated Delayed Action valve to provide a delayed closing to help assist the passage of wheel chair, push-chair or less-abled users. It is suitable for timber fire doors up to 60 minutes, and steel fire doors upto 240 minutes. The product has been independently tested to meet and exceed fire door testing requirements and is backed by a 35 year guarantee for peace of mind.

EN Size	Max Door Width	Max Door Weight
1	750mm	20Kg
<b>2</b>	<b>850mm</b>	<b>40Kg</b>
<b>3</b>	<b>950mm</b>	<b>60Kg</b>
<b>4</b>	<b>1100mm</b>	<b>80Kg</b>
<b>5</b>	<b>1250mm</b>	<b>100Kg</b>
6	1400mm	120Kg

SKU	Size	Finish	Package Type	Qty
DC1214.SE	EN 2-5 Power Size	Silver	Trade Packed	1
DC1214.PNP	EN 2-5 Power Size	Polished Nickel Plated	Trade Packed	1
DC1214.SNP	EN 2-5 Power Size	Satin Nickel Plated	Trade Packed	1

**BS EN 1154:1997 + A1:2002**



**S-40 Overhead Door Closers Surface Mount**

TECHNICAL



Polished Nickel Plated




Satin Nickel Plated



Silver

Max:



The SPÄRKA S-40 Overhead Door Closer is an EN variable power size 2-6 heavy duty door closer making it suitable for doors upto 1400mm wide / or maximum 120Kg. This door closer comes complete with mechanism, cover, armset, parallel arm bracket for mounting on the 'Push' face of the door, installation template and all fixings.

This model also has integrated adjustable valves to independently control the closing and latching speeds. Also with integrated back check valve which provides a cushioning effect for when the door opens too fast and integrated delayed action valve to provide a delayed closing to help assist the passage of wheel chair, push-chair or less-abled users. It is suitable for timber fire doors up to 120 minutes, and steel fire doors upto 240 minutes. The product has been independently tested to meet and exceed fire door testing requirements and is backed by a 35 year guarantee for peace of mind.

EN Size	Max Door Width	Max Door Weight
1	750mm	20Kg
<b>2</b>	<b>850mm</b>	<b>40Kg</b>
<b>3</b>	<b>950mm</b>	<b>60Kg</b>
<b>4</b>	<b>1100mm</b>	<b>80Kg</b>
<b>5</b>	<b>1250mm</b>	<b>100Kg</b>
<b>6</b>	<b>1400mm</b>	<b>120Kg</b>

SKU	Size	Finish	Package Type	Qty
DC1215.SE	EN 2-6 Power Size	Silver	Trade Packed	1
DC1215.SNP	EN 2-6 Power Size	Satin Nickel Plated	Trade Packed	1
DC1215.PNP	EN 2-6 Power Size	Polished Nickel Plated	Trade Packed	1

**BS EN 1154:1997 + A1:2002**

