

## S-50 Overhead Door Closers Slide Arm




The SPÄRKA S-50 Slide Arm Door Closer is an EN variable power size 2-4 door closer making it suitable for doors upto 1100mm wide / or maximum 80Kg. This door closer has a high performance cam & roller mechanism that ensures a very low opening force whilst still maintaining a strong closing force to comply with fire regulations. The slim and compact design makes it less prone to vandalism and more aesthetically pleasing.

This door closer comes complete with mechanism, cover, slide arm channel and connector bar, installation template and all fixings. The closer has integrated adjustable valves to independently control the closing and latching speeds. It is suitable for timber fire doors up to 60 minutes, and steel fire doors upto 240 minutes. The product has been independently tested to meet and exceed fire door testing requirements and is backed by a 35 year guarantee for peace of mind.

### TECHNICAL

Max:



EN Size	Max Door Width	Max Door Weight
1	750mm	20Kg
<b>2</b>	<b>850mm</b>	<b>40Kg</b>
<b>3</b>	<b>950mm</b>	<b>60Kg</b>
<b>4</b>	<b>1100mm</b>	<b>80Kg</b>
5	1250mm	100Kg
6	1400mm	120Kg

SKU	Size	Finish	Package Type	Qty
DC1310.SE	EN 2-4 Power Size	Silver	Trade Packed	1
DC1310.SNP	EN 2-4 Power Size	Satin Nickel Plated	Trade Packed	1
DC1310.PNP	EN 2-4 Power Size	Polished Nickel Plated	Trade Packed	1

### BS EN 1154:1997 + A1:2002



## S-60 Overhead Door Closers Slide Arm




The SPÄRKA S-60 Slide Arm Door Closer is an EN variable power size 2-5 door closer making it suitable for doors upto 1250mm wide / or maximum 110Kg. This door closer has a high performance cam & roller mechanism that ensures a very low opening force whilst still maintaining a strong closing force to comply with fire regulations. The slim and compact design makes it less prone to vandalism and more aesthetically pleasing.

This door closer comes complete with mechanism, cover, slide arm channel and connector bar, installation template and all fixings. The closer has integrated adjustable valves to independently control the closing and latching speeds. It is suitable for timber fire doors up to 60 minutes, and steel fire doors upto 240 minutes. The product has been independently tested to meet and exceed fire door testing requirements and is backed by a 35 year guarantee for peace of mind.

### TECHNICAL

Max:



EN Size	Max Door Width	Max Door Weight
1	750mm	20Kg
<b>2</b>	<b>850mm</b>	<b>40Kg</b>
<b>3</b>	<b>950mm</b>	<b>60Kg</b>
<b>4</b>	<b>1100mm</b>	<b>80Kg</b>
<b>5</b>	<b>1250mm</b>	<b>100Kg</b>
6	1400mm	120Kg

SKU	Size	Finish	Package Type	Qty
DC1311.SE	EN 2-5 Power Size	Silver	Trade Packed	1
DC1311.SNP	EN 2-5 Power Size	Satin Nickel Plated	Trade Packed	1
DC1311.PNP	EN 2-5 Power Size	Polished Nickel Plated	Trade Packed	1

### BS EN 1154:1997 + A1:2002

