

**S-80 Overhead Door Closers Electromagnetic**

TECHNICAL




Polished Nickel Plated



Satin Nickel Plated

Silver

Max:



The SPÄRKA S-80 Electromagnetic Door Closer is an EN power size 4 door closer making it suitable for doors upto 1100mm wide / or maximum 80 Kg. This door closer is designed to be used in either hold-open (ideal for corridor doors) or swing-free mode (ideal for living and bedroom doors) and needs a 24V DC supply along with integration to the fire alarm.

This door closer comes complete with mechanism, cover, armset, parallel arm bracket for mounting on the 'Push' face of the door, hold open and swing free components (choose on installation) installation template and all fixings. The closer has integrated adjustable valves to independently control the closing and latching speeds. It is suitable for timber fire doors up to 60 minutes and steel doors up to 240 minutes. The product has been independently tested to meet and exceed fire door testing requirements and is backed by a 5 year guarantee for peace of mind.

EN Size	Max Door Width	Max Door Weight
1	750mm	20Kg
2	850mm	40Kg
3	950mm	60Kg
<b>4</b>	<b>1100mm</b>	<b>80Kg</b>
5	1250mm	100Kg
6	1400mm	120Kg

SKU	Size	Finish	Package Type	Qty
DC1110.SE	EN 4 Power Size	Silver	Trade Packed	1
DC1110.SNP	EN 4 Power Size	Satin Nickel Plated	Trade Packed	1
DC1110.PNP	EN 4 Power Size	Polished Nickel Plated	Trade Packed	1

**BS EN 1155:1997 + A1:2002**



**SPÄRKA®**

**SPÄRKA Fire Door Hardware.**

